

HLR 200M

HVAC Load Reduction Air Cleaning Module with CO₂ Removal



Improved Air Quality, Lower HVAC Costs


The HLR 200M is enVerid's award-winning air cleaning product that removes CO₂ and contaminants of concern from indoor air so that it can be safely recirculated. This solution reduces first costs and operating costs for new and existing HVAC systems, lowers a building's carbon footprint, and improves indoor air quality while also generating LEED and WELL building credits. Indoor air quality is improved by removing indoor-generated contaminants and reducing the intake of outdoor pollutants. The HLR 200M solution is compliant under ASHRAE 62.1 and IMC 403.2. The HLR 200M module is designed for indoor use. The HLR 15R module (not shown) is an outdoor model designed for rooftop installations.



HLR 200M Module

IMPROVE AIR QUALITY	SAVE ENERGY	REDUCE COSTS	REMOVE CO₂	REDUCE CARBON	EARN LEED/WELL POINTS	NO BYPRODUCTS

Ventilation and Scrubbing



Outside airflow can be reduced using ASHRAE Standard 62.1 IAQP¹ calculations.

How it Works


Indoor Air Scrubbing – One or more HLR 200M modules can be installed on the return air side of an air handling unit (AHU). Air is drawn into the HLR 200M by internal fans, which blow the air through sorbent filters that capture and remove carbon dioxide (CO₂) and contaminants of concern from the air stream. Without producing any byproducts, the HLR 200M then blows clean air back into the return.

Automatic Self-Cleaning – The sorbents are designed to release captured contaminants upon heating. The HLR 200M module is equipped with a built-in heater and performs a periodic regeneration process to clean the sorbents and expel contaminants outside the building. Regeneration is managed for optimal performance and minimal energy use.

Outside Air Intake Reduction – By cleaning recirculated air, outside air ventilation rates can be safely reduced by up to 85%, and new HVAC equipment can be downsized, using the ASHRAE Standard 62.1 IAQ Procedure.

¹ The mass balance analysis is performed per contaminant and per zone to ensure all contaminants are properly maintained below their established limits. These "per zone" outside air CFMs are summed to yield the total ventilation required for the building. enVerid's IAQP calculator makes it easy.

What's Inside the HLR 200M Module?



Broadly Applicable

The 200M is ideally suited to integrate with custom and semi-custom airside systems, including systems with dedicated outside air systems (DOAS) and energy recovery ventilation (ERV) components, in office buildings, schools, and other commercial buildings.



Office Spaces



Higher Education



K-12 Schools



Light Commercial

Proven, Award Winning HLR Technology®

Hundreds of HLR modules have been specified and installed around the world by leading consulting engineers and HVAC contractors. Air cleaning efficiency has been validated by ASHRAE 145.2 testing, and energy savings have been field validated by multiple utilities who have provided incentives for installing HLR modules as well as by the U.S. Department of Energy. Unlike many other air cleaning technologies, independent lab tests show that HLR modules do not produce any byproducts. In 2019, HLR technology received the AHR Expo Product of the Year Award, the most prestigious award for an HVAC product.



200M Module Specifications

GENERAL SPECS

Installation	Mechanical Room or Air Plenum
Construction	Single wall, Insulated, Powder-coated Galvanized Steel
Sorbent Filters per Set	12
Typical Airflow (Adsorption)	1,000 CFM* 1,700 CMH
Typical Airflow (Regeneration)	350 CFM* 595 CMH
Static Pressure Increase to AHU Fan	None
Sound Level	55 dBA
Maximum Allowed External Static Pressure	0.3" WG / 75 Pa
Maintenance	Two-year Filter Replacement
Operating Life	20+ years with scheduled maintenance

*CFM was measured at 0ft elevation and 70 degrees Fahrenheit

COMMUNICATIONS

BMS Integration	BACnet IP with BTL
Security	FIPS 140-2 compliant (2002 standard)

SYSTEM POWER RATINGS (Single Phase)

Voltage (VAC)	Frequency (Hz)	MCA	MOCP
208 V	60 Hz	38.1 A	40 A
277 V	60 Hz	34.3 A	40 A
220-240 V	50 Hz	36.5 A	40 A

SYSTEM POWER CONSUMPTION

	208 V	277 V	220/230/240 V
Adsorption Mode	600 W	600 W	600/600/600 W
Regeneration Mode	6,100 W	7,100 W	5,900/6,400/6,900 W

DIGITAL INPUT (On/Off Signal)

Fire Alarm	Safety Stop for HLR Module
Regen OK	Permits Regen As Scheduled
AHU On	Permits Adsorption When AHU Is On

DIGITAL OUTPUT (On/Off Signal)

Exhaust Fan Start/Stop	Controls External Exhaust Fan
Aux Scrub Fan Start/Stop	Controls External Booster Fan
Unit Status	Signals Module On / Off State
Unit Alarm	Signals Normal Or Alarm State

WEIGHTS

Module Shipping Weight	505 lbs	229 kg
Filter Shipping Weight	200 lbs	91 kg
Installation (Module Only)	393 lbs	178 kg
Operating (With Filters)	593 lbs	269 kg

DIMENSIONS (Front View)

Height (Allow Additional 21" Clearance for Elbow)	72" / 1,829 mm
Width (Allow Additional 36" Clearance for Control Panel Service)	48" / 1,219 mm
Depth (Allow Additional 36" Clearance for Filter Service)	27" / 686 mm
Ducts	10" x 14" w/ 1.0" flange 254 mm x 356 mm w/ 25 mm flange

CERTIFICATIONS

HLR Module Safety	UL 1995:2015 Ed.5 CSA C22.2#236:2015 ed.5
Filter Bank and Filters	UL 900:2015 Ed.8
Air Cleaning Efficiency	ASHRAE 145.2

ASHRAE Standard Compliance

Standard 62.1 for Ventilation & Acceptable Indoor Air Quality

All of enVerid's HLR products are fully compliant under ASHRAE Standard 62.1. By using ASHRAE's performance-based Indoor Air Quality Procedure (IAQP) rather than the prescriptive Ventilation Rate Procedure (VRP), engineers can calculate a minimum ventilation rate that optimizes indoor air quality and energy efficiency. Introduced in 1981, IAQP determines outdoor air intake rates based on an analysis of contaminant sources and air cleaning capacity to stay below recommended contaminant concentration limits. Tools developed by enVerid's in-house engineering team, including enVerid's online IAQP Calculator, streamline the application of IAQP for engineers.

Standard 145.2 for Assessing the Performance of Gas-Phase Air Cleaning Systems

HLR technology is one of the only air cleaning technologies to have undergone independent lab tests for cleaning efficiency using ASHRAE Standard 145.2. Independent labs have conducted ASHRAE 145.2 single-pass efficiency testing for all the contaminants of concern required to maintain acceptable indoor air quality in buildings.

enverid.com · 1.617.795.4000 · info@enverid.com

Energy Savings. Air Quality.

enVerid Systems, the leading provider of sustainable indoor air quality (IAQ) solutions, helps buildings achieve air quality goals, save money, and reduce energy consumption and carbon emissions. Its flagship HVAC Load Reduction® (HLR) modules are award-winning air cleaners that deliver up to 40% HVAC energy savings and superior indoor air quality in new and existing buildings. For new HVAC systems, HLR modules also enable immediate capital cost savings. At the core of all HLR modules is enVerid Sorbent Ventilation Technology™ (SVT™), uniquely designed to capture gaseous contaminants that degrade indoor environmental quality. enVerid's HEPA air filtration products remove particulate and microorganism contamination, including viruses, from indoor air without the significant cost of upgrading mechanical systems and increasing mechanical ventilation rates. enVerid's products are deployed in commercial, academic, and government buildings globally. Its air cleaning products are ASHRAE Standard 62.1, LEED® and WELL compliant and eligible for utility rebates. For more information, please visit enverid.com.